

# OX BLUE THUNDER

High Strength, Hardox Material

## OX BODIES



"As Strong As An Ox"®



## Rugged Reliability

- Maximize payload with the reduced body weight of high-strength Hardox materials and contemporary elliptical design.
- Stand up to harsh environments with corrosion-resistant continuous welds.
- Depend on the durability of the superior dent-resistant, ultra-strong I-Beam understructure.
- Choose the heated option to keep materials flowing smoothly throughout the year.

A  **TBEI** BRAND  
TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.

[www.oxbodies.com](http://www.oxbodies.com)

# OX BLUE THUNDER

## Standard Features

- 84" Wide
- 10" I Beam Understructure
- 3/16" Hardox Floor
- 10 ga Hardox Sides & Rear
- 10 ga Van 80 Front
- Two Horizontal Rear Braces
- Flat Steel Lower Walkrail
- Rigid Ladder/Steps Inside (Drivers' Front)
- Steel Fender
- ½ Cab Shield
- Telescopic hoist with chrome cylinder
- 9" Floor to Side Radius
- Two Year Warranty
- Epoxy primer and polyurethane top coat

## Standard Sizes


- Lengths from 13' thru 21'
- Side heights of 42", 48", 54"
- Rear heights of 48", 54", 60"

## Basic Options

- Heated understructure, manual or temperature regulated
- Electric or manual tarp
- Steerable or rigid lift axles, with wheels and tires optional
- Controls; all air, hot-shift pto or any combination
- Wood, steel or tread-brite aluminum side boards
- ¾ Cab shield
- Pintle hitches to 50 ton



Full depth rear corner post for stability and durability



Continuous welds minimize moisture build up preventing rust

### TYPICAL WEIGHT & CAPACITY

LENGTH (ft)	13	14	15	16	17	18	19	20	21
Side/Front/Rear Height (in)*	48/54/54	48/54/54	48/54/54	48/54/54	48/54/54	48/54/54	48/54/54	48/54/54	48/54/54
Body Capacity (cubic yds)	13.5-15	14-16	15.5-17.5	16.5-18.5	17.5-20	18.5-21	19.5-22	20.5-23.5	22-24.5
Weight (lbs)	2870	2992	3114	3235	3357	3479	3602	3749	3907

\*Additional specifications available based on sizes as listed above.

### HOIST SPECIFICATIONS

	T63113	T63131	T63148	T73129	T73147	T74167	T74191
NTEA PERFORMANCE CLASS	110	110	120	120	120	120	120
NUMBER OF STAGES	3	3	3	3	3	4	4
ACTIVE STAGE SIZES (in)	6,5,4	6,5,4	6,5,4	7,6,5	7,6,5	7,6,5,4	7,6,5,4
TOTAL STROKE (in)	113	131	148	129	147	167	191
CYLINDER RATED PRESSURE (psi)	2,500	2,500	2,500	2,500	2,500	2,500	2,500
STD. PUMP GPM @ 1000 RPM	20	20	20	25	25	25	25
STD. RESERVOIR SIZE (gal)	28	28	28	40	40	40	40
RECOMMENDED BODY LENGTH (ft)	13-14.5	15-15.5	16-17.5	15-15.5	16-17.5	18-19.5	20-21.5
APPROXIMATE WEIGHT (lbs)	867	900	930	1010	1042	1096	1128

### HOIST LOAD CAPACITY IN TONS\*

HOIST MODEL	NTEA CLASS	BODY LENGTH (ft)								
		13	14	15	16	17	18	19	20	21
T63113	110	42.0	37.6							
T63131	110			38.1						
T63148	120				39.8	36.6				
T73129	120			59.3						
T73147	120				62.1	57.1				
T74167	120						41.4	38.4		
T74191	120								40.7	38.1

\*Assumes water-level load, 50° dump angle and includes body weight. Models and options are subject to change without notice.

# OX BODIES



"As Strong As An Ox" ®

719 Columbus Street East • Fayette, AL 35555  
Phone 205-932-5720 • 800-844-2519

Sold by: