

# THE MAVERICK

Custom built square dump bodies

## OX BODIES



"As Strong As An Ox"®



### Rugged Reliability

- Release materials quickly and easily with a 45-degree floor-to-side bevel included in this classic square body design.
- Minimize material hang-up, when releasing the load, through an innovative one-piece floor construction.
- Choose from available options to easily configure for all vocational applications.

A  BRAND  
TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.

[www.oxbodies.com](http://www.oxbodies.com)

## Standard Features

- 8'-19' Lengths, 5-30 yard capacity
- 10 Gauge sides and front material
- 3/16" Floor material
- 3/16" Tailgate material
- Vertical side bracing
- 2" x 8" x 3/16" Tubing longills
- 1 1/2" x 3" x 11 Gauge crossmembers
- 4" x 4" x 11 Gauge top rail
- Air operated tailgate
- 8" Board pockets
- 8"-15" Apron
- Tarp tie-down strips
- Ladders & steps at front of body
- 24"-36" Cab shield
- Front doghouse hoist
- Custom wiring harness
- Cable to pump, air-shift pto controls
- Federal standard 108, all LED lights
- One year warranty
- Epoxy primer and polyurethane top coat

## Basic Options

- Air operated hi-lift tailgate
- 2-Way (barn-door) tailgate
- DuraClass Double Arm Hoist, 1824HD underbody
- Ribbed (horizontal braced) sides
- Electric or manual tarp
- Insulated sides & front
- Controls; all air, hot-shift pto or any combination
- Wood, steel or tread-brite aluminum side boards
- 42" Cab shield
- Heavy duty push bumper apron
- Tread-brite aluminum skirt covers
- Inverted trunnion hoist
- 1/4", 3/8", or 1/2" Hardox floor
- Crossmemberless type body
- Body vibrator
- 1/2" Body liner
- Steerable or rigid lift axles, with wheels and tires optional
- One-way or two-way freight



Heavy duty push bumper apron.



Direct mount, front lift telescopic hoist.

### HOIST SPECIFICATIONS

	1824HD	6382	63111	63120T	63130	63150T	63160T	73110	74135	74161
<b>NTEA PERFORMANCE CLASS</b>	60	70	80	90	100	100	100	110	100	110
<b>NUMBER OF STAGES</b>	1	3	3	3	3	3	3	3	4	4
<b>ACTIVE STAGE SIZES(IN.)</b>	8	5,4,3	5,4,3	5,4,3	5,4,3	5,4,3	5,4,3	6,5,4	6,5,4,3	6,5,4,3
<b>TOTAL STROKE(IN.)</b>	24	82	111	120	130	150	160	110	135	161
<b>CYLINDER RATED PRESSURE(PSI)</b>	1,500	2,000	2,000	2,000	2,000	2,000	2,000	2,000	2,000	2,000
<b>STD.PUMP GPM @ 1800 RPM</b>	30	29	48	48	48	48	48	48	48	48
<b>RECOMMENDED BODY LENGTH(FT.)*</b>	9-14	10-11	12-14	12-13	15-16	15-16	17	14	15-17	17-19
<b>APPROXIMATE WEIGHT(LBS.)</b>	228	250	260	270	295	290	290	335	370	405

### HOIST LOAD CAPACITY IN TONS\*\*

HOIST MODEL	NTEA CLASS	BODY LENGTH (FT.)												
		9	10	11	12	13	14	15	16	17	18	19		
1824HD	60	24.2	21.9	19.6	17.5	15.8	14.4							
6382	70		32.3	28.5										
63111	80				33.3	29.7	26.2							
63120T	90				32.4	31.3								
63130	100							24.2	23.2					
63150T	100							31.2	29.0					
63160T	100									28.5				
73110	110						42.1							
74135	100							30.5	27.9	25.5				
74161	110									30.3	28.1	26.5		

# OX BODIES



"As Strong As An Ox" ®

719 Columbus Street East • Fayette, AL 35555  
Phone 205-932-5720 • 800-844-2519

\*All telescopic hoists w/doghouse reservoir.  
\*\*Capacities based on water-level load, 12" overhang, 50 degree dump angle.  
Specifications subject to change.

Sold by: