

THE STAMPEDE XD

Custom built elliptical dump bodies

OX BODIES



"As Strong As An Ox"®



Rugged Reliability

Benefit from superior support and construction highlighted by the elliptical design (26" radius sides) with ¼ AR 450 Hardox material.

- Withstand extreme circumstances and tough conditions with the Stampede XD's precision engineering.
- Depend on guaranteed durability, a result of the expert craftsmanship that goes into every body.

A  **TBEI** BRAND
TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.

www.oxbodies.com

STAMPEDE XD

Standard Features

- 8'-19' Lengths, 8-30 yard capacity
- ¼" Hardox 450 material interior
- 26" Radius sides
- Front doghouse hoist
- Air operated tailgate
- **Overlapped floor seams with double welds**
- **Full length ¾" outer skirts**
- **8" I-beam @24 lbs per ft. longills**
- **¼" Wall 4" x 4" tubing, diamond mounted top rail**
- **Full width floor welded solid to skirts**
- **Dual air tailgate cylinders**
- Driver's side step(s) & grab handle(s), plus interior step(s)
- Heavy duty push bumper apron
- Custom wiring harness
- Cable to pump, air-shift pto controls
- Federal standard 108 all LED lights

- One year warranty
- Epoxy primer and polyurethane top coat

Basic Options

- Air operated hi-lift tailgate
- Electric or manual tarp
- Steerable or rigid lift axles, with wheels and tires optional
- Controls; all air, hot-shift pto or any combination
- Wood, steel or tread-brite aluminum side boards
- 24"-42" Cab shield
- Inverted trunnion hoist
- Tread-brite aluminum skirt covers
- One-way or two-way freight
- Pintle hitches to 50 ton



Direct mount, front lift hydraulic hoist.



Elliptical style dump body.

HOIST SPECIFICATIONS

	6382	63111	63120T	63130	63150T	63160T	73110	74135	74161
NTEA PERFORMANCE CLASS	70	80	90	100	100	100	110	100	110
NUMBER OF STAGES	3	3	3	3	3	3	3	4	4
ACTIVE STAGE SIZES(IN.)	5,4,3	5,4,3	5,4,3	5,4,3	5,4,3	5,4,3	6,5,4	6,5,4,3	6,5,4,3
TOTAL STROKE(IN.)	82	111	120	130	150	160	110	135	161
CYLINDER RATED PRESSURE(PSI)	2,000	2,000	2,000	2,000	2,000	2,000	2,000	2,000	2,000
STD.PUMP GPM @ 1800 RPM	29	48	48	48	48	48	48	48	48
RECOMMENDED BODY LENGTH(FT.)*	10-11	12-14	12-13	15-16	15-16	17	14	15-17	17-19
APPROXIMATE WEIGHT(LBS.)	250	260	270	295	290	290	335	370	405

HOIST LOAD CAPACITY IN TONS**

HOIST MODEL	NTEA CLASS	BODY LENGTH (FT.)									
		10	11	12	13	14	15	16	17	18	19
6382	70	32.3	28.5								
63111	80			33.3	29.7	26.2					
63120T	90			32.4	31.3						
63130	100						24.2	23.2			
63150T	100						31.2	29.0			
63160T	100								28.5		
73110	110					42.1					
74135	100						30.5	27.9	25.5		
74161	110								30.3	28.1	26.5

*All hoists w/doghouse reservoir.
**Capacities based on water-level load, 12" overhang, 50 degree dump angle.
Specifications subject to change.

OX BODIES



"As Strong As An Ox" ®

719 Columbus Street East • Fayette, AL 35555
Phone 205-932-5720 • 800-844-2519

Sold by: